Walk-In Cooler Swing Doors

Specification Sheet

Construction

- 26-gauge stucco-embossed steel skins over high-density rigid foam insulated core
- Prehung in frame with all hardware mounted, aligned, and adjusted before shipment
- Diamond-plate kick plates on interior and exterior faces
- Magnetic perimeter gasket with adjustable double-sweep bottom seal
- Skins: white stucco embossed (standard) or stainless steel with white belly

Frame Options

- Plug frame: fills the existing rough opening; standard for replacements
- Jamb frame: wraps the panel edges; standard for newly cut openings
- Frame depth built to your wall thickness (3.5″ to 6″ typical; specify at order)

Hardware

- Chrome NSF-approved cam-rise hinges, self-closing
- Lockable latch with interior safety release (meets safety egress requirements)
- Hydraulic door closer, factory adjusted
- Left- or right-hinge configuration, specified at order

Ordering & Tolerances

- Built to your rough opening; approx. 1″ rough-opening tolerance
- Measure width at three heights and height at both sides; use smallest of each
- Lead time approx. 3 weeks; ships nationwide by freight, liftgate available
- Custom sizes built at no size upcharge — call 844-328-3766

Standard Size Range (rough opening, W × H, inches)

Widths	Heights	Oversize
30 / 32 / 33 / 34 / 35 / 36	76 / 78 / 80 / 82 / 84	47×120
38 / 40 / 42 / 45 / 47	78 / 80 / 84 / 90 / 96	52×130 · 52×144
52 / 54 / 60 / 70 / 72	96 / 108	72×108

All listed sizes are stocked patterns; any size between or beyond these is built to order at no size upcharge.